

MARK SCHEME for the May/June 2013 series

9702 PHYSICS

9702/43

Paper 4 (A2 Structured Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2013 series for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level components and some Ordinary Level components.

Page 2	Mark Scheme	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2013	9702	43

Section A

- 1 (a) region of space area / volume where a mass experiences a force B1 B1 [2]
- (b) (i) force proportional to product of two masses M1
force inversely proportional to the square of their separation M1
either reference to point masses *or* separation \gg 'size' of masses A1 [3]
- (ii) field strength = GM / x^2 **or** field strength $\propto 1 / x^2$ C1
ratio = $(7.78 \times 10^8)^2 / (1.5 \times 10^8)^2$ C1
= 27 A1 [3]
- (c) (i) *either* centripetal force = $mR\omega^2$ and $\omega = 2\pi / T$ B1
or centripetal force = mv^2 / R and $v = 2\pi R / T$ B1
gravitational force provides the centripetal force M1
either $GMm / R^2 = mR\omega^2$ *or* $GMm / R^2 = mv^2 / R$ A0 [3]
 $M = 4\pi^2 R^3 / GT^2$
(allow working to be given in terms of acceleration)
- (ii) $M = \{4\pi^2 \times (1.5 \times 10^{11})^3\} / \{6.67 \times 10^{-11} \times (3.16 \times 10^7)^2\}$ C1
= 2.0×10^{30} kg A1 [2]
- 2 (a) obeys the equation $pV = \text{constant} \times T$ *or* $pV = nRT$ M1
 p , V and T explained A1
at all values of p , V and T /fixed mass/ n is constant A1 [3]
- (b) (i) $3.4 \times 10^5 \times 2.5 \times 10^3 \times 10^{-6} = n \times 8.31 \times 300$ M1
 $n = 0.34$ mol A0 [1]
- (ii) for total mass/amount of gas
 $3.9 \times 10^5 \times (2.5 + 1.6) \times 10^3 \times 10^{-6} = (0.34 + 0.20) \times 8.31 \times T$ C1
 $T = 360$ K A1 [2]
- (c) when tap opened B1
gas passed (from cylinder B) to cylinder A M1
work done on gas in cylinder A (and no heating) A1 [3]
so internal energy and hence temperature increase

Page 3	Mark Scheme	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2013	9702	43

- 3 (a) (i) 1. amplitude = 1.7 cm A1 [1]
2. period = 0.36 cm C1
frequency = 1/0.36 A1 [2]
= 2.8 Hz
- (ii) $a = (-)\omega^2 x$ and $\omega = 2\pi/T$ C1
acceleration = $(2\pi/0.36)^2 \times 1.7 \times 10^{-2}$ M1
= 5.2 m s^{-2} A0 [2]
- (b) graph: straight line, through origin, with negative gradient M1
from $(-1.7 \times 10^{-2}, 5.2)$ to $(1.7 \times 10^{-2}, -5.2)$ A1 [2]
(if scale not reasonable, do not allow second mark)
- (c) either kinetic energy = $\frac{1}{2}m\omega^2(x_0^2 - x^2)$ B1
or potential energy = $\frac{1}{2}m\omega^2 x^2$ and potential energy = kinetic energy C1
 $\frac{1}{2}m\omega^2(x_0^2 - x^2) = \frac{1}{2} \times \frac{1}{2}m\omega^2 x_0^2$ or $\frac{1}{2}m\omega^2 x^2 = \frac{1}{2} \times \frac{1}{2}m\omega^2 x_0^2$
 $x_0^2 = 2x^2$
 $x = x_0 / \sqrt{2} = 1.7 / \sqrt{2}$
= 1.2 cm A1 [3]
- 4 (a) work done moving unit positive charge M1
from infinity (to the point) A1 [2]
- (b) (gain in) kinetic energy = change in potential energy B1
 $\frac{1}{2}mv^2 = qV$ leading to $v = (2Vq/m)^{1/2}$ B1 [2]
- (c) either $(2.5 \times 10^5)^2 = 2 \times V \times 9.58 \times 10^7$ C1
 $V = 330 \text{ V}$ M1
this is less than 470 V and so 'no' A1 [3]
- or $v = (2 \times 470 \times 9.58 \times 10^7)^{1/2}$ (C1)
 $v = 3.0 \times 10^5 \text{ m s}^{-1}$ (M1)
this is greater than $2.5 \times 10^5 \text{ m s}^{-1}$ and so 'no' (A1)
- or $(2.5 \times 10^5)^2 = 2 \times 470 \times (q/m)$ (C1)
 $(q/m) = 6.6 \times 10^7 \text{ C kg}^{-1}$ (M1)
this is less than $9.58 \times 10^7 \text{ C kg}^{-1}$ and so 'no' (A1)

Page 4	Mark Scheme	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2013	9702	43

- 5 (a) (uniform magnetic) flux normal to long (straight) wire carrying a current of 1 A (creates) force per unit length of 1 N m^{-1} M1
A1 [2]
- (b) (i) flux density $= 4\pi \times 10^{-7} \times 1.5 \times 10^3 \times 3.5$
 $= 6.6 \times 10^{-3} \text{ T}$ C1
A1 [2]
- (ii) flux linkage $= 6.6 \times 10^{-3} \times 28 \times 10^{-4} \times 160$
 $= 3.0 \times 10^{-3} \text{ Wb}$ C1
A1 [2]
- (c) (i) (induced) e.m.f. proportional to rate of change of (magnetic) flux (linkage) M1
A1 [2]
- (ii) e.m.f. $= (2 \times 3.0 \times 10^{-3}) / 0.80$
 $= 7.4 \times 10^{-3} \text{ V}$ C1
A1 [2]
- 6 (a) (i) to reduce power loss in the core due to eddy currents/induced currents B1
B1 [2]
- (ii) *either* no power loss in transformer
or input power = output power B1 [1]
- (b) *either* r.m.s. voltage across load $= 9.0 \times (8100 / 300)$
peak voltage across load $= \sqrt{2} \times 243$
 $= 340 \text{ V}$ C1
A1 [2]
- or* peak voltage across primary coil $= 9.0 \times \sqrt{2}$
peak voltage across load $= 12.7 \times (8100/300)$
 $= 340 \text{ V}$ (C1)
(A1)
- 7 (a) (i) lowest frequency of e.m. radiation giving rise to emission of electrons (from the surface) M1
A1 [2]
- (ii) $E = hf$ C1
threshold frequency $= (9.0 \times 10^{-19}) / (6.63 \times 10^{-34})$
 $= 1.4 \times 10^{15} \text{ Hz}$ A1 [2]
- (b) *either* $300 \text{ nm} \equiv 10 \times 10^{15} \text{ Hz}$ (and $600 \text{ nm} \equiv 5.0 \times 10^{14} \text{ Hz}$)
or $300 \text{ nm} \equiv 6.6 \times 10^{-19} \text{ J}$ (and $600 \text{ nm} \equiv 3.3 \times 10^{-19} \text{ J}$)
or zinc $\lambda_0 = 340 \text{ nm}$, platinum $\lambda_0 = 220 \text{ nm}$ (and sodium $\lambda_0 = 520 \text{ nm}$)
emission from sodium and zinc M1
A1 [2]
- (c) each photon has larger energy M1
fewer photons per unit time M1
fewer electrons emitted per unit time A1 [3]

Page 5	Mark Scheme	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2013	9702	43

- 8 (a) two (light) nuclei combine to form a more massive nucleus M1
A1 [2]
- (b) (i) $\Delta m = (2.01410\text{ u} + 1.00728\text{ u}) - 3.01605\text{ u}$
 $= 5.33 \times 10^{-3}\text{ u}$
energy $= c^2 \times \Delta m$ C1
 $= 5.33 \times 10^{-3} \times 1.66 \times 10^{-27} \times (3.00 \times 10^8)^2$ C1
 $= 8.0 \times 10^{-13}\text{ J}$ A1 [3]
- (ii) speed/kinetic energy of proton and deuterium must be very large so that the nuclei can overcome electrostatic repulsion B1
B1 [2]

Section B

- 9 (a) (i) light-dependent resistor/LDR B1 [1]
- (ii) strain gauge B1 [1]
- (iii) quartz/piezo-electric crystal B1 [1]
- (b) (i) resistance of thermistor decreases as temperature increases M1
either $V_{\text{OUT}} = V \times R / (R + R_T)$
or current increases and $V_{\text{OUT}} = IR$ A1
 V_{OUT} increases A1 [3]
- (ii) *either* change in R_T with temperature is non-linear
or V_{OUT} is not proportional to R_T / change in V_{OUT} with R_T is non-linear
so change is non-linear M1
A1 [2]
- 10 (a) sharpness: how well the edges (of structures) are defined B1
contrast: difference in (degree of) blackening between structures B1 [2]
- (b) e.g. scattering of photos in tissue/no use of a collimator/no use of lead grid
large penumbra on shadow/large area anode/wide beam
large pixel size
(any two sensible suggestions, 1 each) B2 [2]
- (c) (i) $I = I_0 e^{-\mu x}$ C1
ratio $= \exp(-2.85 \times 3.5) / \exp(-0.95 \times 8.0)$ C1
 $= (4.65 \times 10^{-5}) / (5.00 \times 10^{-4})$
 $= 0.093$ A1 [3]
- (ii) *either* large difference (in intensities)
or ratio much less than 1.0
so good contrast M1
A1 [2]
- (answer given in (c)(ii) must be consistent with ratio given in (c)(i))

Page 6	Mark Scheme	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2013	9702	43

- 11 (a) (i) amplitude of the carrier wave varies
(in synchrony) with the displacement of the information signal M1
A1 [2]
- (ii) e.g. more than one radio station can operate in same region/less interference
enables shorter aerial
increased range/less power required/less attenuation
less distortion
(any two sensible answers, 1 each) B2 [2]
- (b) (i) frequency = 909 kHz C1
wavelength = $(3.0 \times 10^8) / (909 \times 10^3)$
= 330 m A1 [2]
- (ii) bandwidth = 18 kHz A1 [1]
- (iii) frequency = 9000 Hz A1 [1]
- 12 (a) for received signal, $28 = 10 \lg(P / \{0.36 \times 10^{-6}\})$ C1
 $P = 2.3 \times 10^{-4} \text{ W}$ A1 [2]
- (b) loss in fibre = $10 \lg(\{9.8 \times 10^{-3}\} / \{2.27 \times 10^{-4}\})$ C1
= 16 dB A1 [2]
- (c) attenuation per unit length = $16 / 85$
= 0.19 dB km^{-1} A1 [1]